

# TouchPro® Pro-G Glass PCAP

7" to 22"



16 ×16

16 pt Multi-Touch



7" to 22" (Standard & Wide Format)



2 Glass Solution (2GS)

## **Product Overview**

The Elo TouchPro Pro-G Projected Capacitive (PCAP) touch technology offers a fast and sensitive response and professional-grade reliability combined with a stylish, sleek design. Elo's Pro-G PCAP is designed for the rigors of commercial applications. The glass-glass solution (2GS) offers pristine optical clarity, high touch durability and long term stability over temperature. Pro-G is available in standard screen sizes up to 22-inches with 16-point multi-touch capabilities. Elo's TouchPro line offers a complete PCAP solution including touch screen, controller, drivers for various operating systems and software utilities resulting in shorter development and integration time. The complete integration guide provides guidelines to simplify integration and avoid typical issues such as EMI from sources such as the power supply or LCD screen. Elo also offers a wide range of customization options to meet your requirements including screen dimensions, cover glass thickness, LCD bonding, branding and surface treatments such as anti-glare.



### **Controller** 8200-Series up to 22" 9200-Series up to 22"

#### **Elo TouchPro Pro-G Glass Projected Capacitive Specifications**

| Touchscreen         |   |
|---------------------|---|
| Size Range          | 7" to 22"                               |
| Light Transmittance | ≥ 90%                                   |
| Haze                | < 1%                                    |
| Overall Thickness   | 3.1mm                                   |
| Cover Glass         | 1.8mm                                   |
| Durability          | Over 50 million touches in one location |

| Touch Performance   | Touch Performance                      |  |
|---------------------|--|--|
| Input Methods       | Finger, gloved hand, or passive stylus |  |
| Number of Touches   | Up to 16                               |  |
| Report Rate         | ≥ 100Hz                                |  |
| Positional Accuracy | ± 1.5mm                                |  |

| Electrical |                            |  |
|------------|----------------------------|--|
|            | Communication Interface(s) | USB (Standard), I2C, HID Over I2C (Optional) |

| Environmental    |  |
|------------------|--|
| Touchscreen      | Operating Temp -20 to 70C; RH < 90% (non-condensing) |
| Controller       | Operating Temp -20 to 70C (Non Condensing)           |
| Safety Approvals | UL   |

| Software          |  |
|-------------------|--|
| Operating Systems | Windows XP, Windows 7, Windows 8, Linux, Android   |
| Utilities         | Multiple monitor, various touch modes, touch zones |

## 2 year limited warranty

| Benefits |  |
|----------|--|
|          | 16-point multi-touch                           |
|          | Fast and sensitive touch response              |
|          | Excellent optical clarity                      |
|          | Long-term stable operation over temperature    |
|          | Optional surface treatments such as anti-glare |

| Applications                                 |
|--|
| Interactive digital signage                  |
| Gaming and lottery terminals                 |
| Industrial automation                        |
| Medical equipment                            |
| Point-of-information & transportation kiosks |
| POS solutions                                |
| Education/white board                        |
| Self-service/service automation kiosks       |

To find out more about our extensive range of Elo touch solutions, go to **elotouch.com**, or call the office nearest you.

**North America** Tel +1 408 597 8000

Fax +1 408 597 8000 Fax +1 408 597 8050 elosales.na@elotouch.com Europe

Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49 elosales@elotouch.com Asia-Pacific

Tel +86 (21) 3329 1385 Fax +86 (21) 3329 1400 www.elotouch.com.cn **Latin America** 

Tel +52 55 2281 6958 www.elotouch.com



