



Product Overview

All-in-one, the Elo PayPoint is your register, cash drawer, credit card reader, barcode scanner, receipt printer, and customer facing display for your favorite point of sale (POS) software application. PayPoint integrates with all your back-office applications, leveraging the management and security of Microsoft Windows.

Designed for ease of serviceability, PayPoint provides easy access to memory and storage compartments. Performance for point of sale applications is powered by an Intel Celeron quad-core processor. The flip-for-signature touch screen encourages shopper engagement and electronic receipt delivery. Retail peripheral expansion is supported by additional serial and USB connections.

Deploy your favorite POS software on a stylish all-in-one platform that works as good as it looks

Accept new forms of payment

Deploy proximity marketing

Elo PayPoint* for Windows*

Specifications	
Color	White
Processor	Intel 2GHz Celeron Quad-Core J1900; 2MB L2 Cache; fanless
Memory (RAM)	4GB 1600MHz DDR3L SO-DIMM (upgradeable to 8GB on single slot)
Storage	128GB SSD
Display	13.3" diagonal, Active matrix TFT LCD (LED), 16x9
Useful Screen Area (W x H)	11.55" x 6.50" (293.47mm x 165.08mm)
Native (optimal) Resolution	Full HD 1920 x 1080
Colors	262,144
Touch Technology	Projected Capacitive (PCAP) zero-bezel - up to 10-touch
Brightness (typical)	LCD panel: 330 nits; PCAP: 300 nits
Response Time-total (typical)	25ms
Viewing Angle (typical)	Horizontal: 170° Vertical: 170°
Contrast Ratio (typical)	700:1
Connectivity	Wi-Fi 802.11ac & Bluetooth 4.0
Serial Ports	1 x native serial port (RJ-45) with DB9 adapter cable included
USB Ports	1 x USB 2.0 (side) and 2 x USB 2.0 (bottom)
Ethernet Port	1 x LAN RJ45 (Gigabit)
Cash Drawer	4 bill trays, 5 coin compartments, 1 check slot, mechanical locking key
Printer	Thermal 2 1/4" (58mm); accepts 2" (50mm) thermal paper roll
Bar Code Reader	1D Scanner
MSR	3-track encryptable - encryption key and verification of encryption is customer responsibility
Customer Facing Display	2 line, 16 character display
Operating System Options	No Operating System; Windows Embedded POSReady 7; Windows Embedded Enterprise 7
Dimensions	13.5" x 15.7" (343mm x 399mm)
Weight	14.4 lbs (6.5 lkg) unpackaged; 20.0 lbs (9.07kg) packaged
Shipping Box Dimensions	18.9" x 11.2" x 16.5" (480mm x 285mm x 420mm)
Temperature	Operating: 32°F to 95°F (0°C to 35°C); Storage -4°F to 140°F (-20°C to 60°C)
Humidity (non-condensing)	Operating: 10% to 90%; Storage: 0% to 95%
Warranty	3 years
MTBF	50,000 hours demonstrated
Power Supply	Internal AC input voltage: 100-240VAC; Input frequency: 50-60Hz; 75W max.
What's in the Box	PayPoint for Windows (includes cash drawer, printer, MSR, bar code scanner, customer facing display), RJ45 to DB9 cable fo external printer and other devices, Ethernet cable, Power cable, 2 receipt paper rolls, 2 cash drawer keys, Quick Install Guid

To find out more about our extensive range of Elo touch solutions, go to **elotouch.eu**, or call the office nearest you.

North America

Tel +1 408 597 8000 Fax +1 408 597 8050 elosales.na@elotouch.com Europe

Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49 elosales@elotouch.com Asia-Pacific

Tel +86 (21) 3329 1385 Fax +86 (21) 3329 1400 www.elotouch.com.cn **Latin America**

Tel +1 786-923-0251 Fax +1 305-931-0124 elosales.latam@elotouch.com



