

# 1004LS 10-inch LCD

**Touchscreen Monitor** 



Optically-bonded display



Ultra-thin design



### **Commercial-grade**

## **Product Overview**

The Elo 1004LS 10-inch Full HD touchscreen monitor delivers commercial-grade durability, brilliant display clarity with state-of-the-art optical bonding and a minimalistic design perfect for any application. Backed by a three-year warranty, the 1004LS offers an energy efficient TouchPro® PCAP touchscreen enabling up to 10 simultaneous touches. With a clean design aesthetic, dual built-in speakers, flexible mounting options and increased viewing comfort with low blue light, the 1004LS touchscreen is well-suited for POS, HMI, interactive digital signage and self-service.

USB-C interface that provides touch, video and power connectivity

Durable IK07 design with chemicallystrengthened scratch resistant glass

Narrow border touchscreen with edge-to-edge glass

#### **1004LS 10-inch LCD Touchscreen Monitor**

| Specifications                        |   |  |  |  |
|---------------------------------------|---|--|--|--|
| Color                                 | Dark gray   |  |  |  |
| Diagonal Size                         | 10.1" / 256.54 mm   |  |  |  |
| Active Touch Area                     | 8.54" x 5.34" / 216.96 mm x 135.60 mm   |  |  |  |
| LCD Technology                        | Active matrix TFT LCD   |  |  |  |
| Touch Technology                      | TouchPro PCAP   |  |  |  |
| Number of Touches                     | 10 Touches  |  |  |  |
| Aspect Ratio                          | 16:10   |  |  |  |
| Native Resolution                     | 1280 × 800  |  |  |  |
| Preset Video Timings                  | 640x480 60Hz, 800x500 60Hz, 800x600 60Hz, 1024x768 60Hz, 1280x800 60Hz, 1280x720 60Hz, 1280x1024 60Hz, 1366x768 60Hz, 60Hz RB, 1440x900 60Hz, 60Hz RB, 1680x1050 60Hz, 60Hz RB, 1920x1080 60Hz  |  |  |  |
| Number of Colors                      | 16.7M   |  |  |  |
| Brightness (typical)                  | Panel: 400 nits; with TouchPro PCAP: 360 nits   |  |  |  |
| Response Time (Tr + Tf) (typical)     | 30 msec   |  |  |  |
| Viewing Angle (typical)               | Horizontal: 85°/85° or 170° total; Vertical: 85°/85° or 170° total  |  |  |  |
| Contrast Ratio (typical)              | 800:1   |  |  |  |
|                                       | Accessible through touch OSD, and press Menu button to pop up touch OSD diagram.<br>Controls: Menu, Power<br>Settings: Brightness, Contrast, Color Temperature, Low Blue Light, Volume, Mute, OSD Timeout, OSD Language, Sharpness, Touch on Sleep mode   |  |  |  |
| On-Screen Display (OSD)               | ON/OFF, Power LED ON/OFF, Recall Defaults<br>Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese<br>Lockouts: OSD, Power  |  |  |  |
| I/O Ports                             | USB Type-C connector  |  |  |  |
| Video                                 | USB Type-C connector<br>Input Video Horizontal Sync frequency range: 30 – 60KHz<br>Input Video Vertical Sync (frame rate) frequency range: 60Hz   |  |  |  |
| Speakers                              | 2 x 2W internal speakers  |  |  |  |
| Power                                 | Power Delivery compatible via USB Type-C connector<br>Input range: (5V±5% 3A/9V±5% 3A/15V±5% 1.8A/20V±5% 1.35A)<br>ON (Default - 100% Brightness): 6.6W<br>SLEEP: 0.8 W<br>OFF: 0.15 W  |  |  |  |
| Dimensions with Stand (H x W x D)     | Without VESA Adapter: 9.45" x 6.42" x 0.59" / 239.94 mm x 163 mm x 15 mm<br>With VESA Adapter: 9.45" x 6.42" x 0.79" / 239.94 mm x 163 mm x 20 mm   |  |  |  |
| Shipping Dimensions                   | 12.28" x 8.74" x 3.03" / 312 mm x 222 mm x 77 mm  |  |  |  |
| Weight                                | Unpackaged: 1.32 lbs / 0.6 kg<br>Packaged: 2.45 lbs / 1.11kg  |  |  |  |
| Mounting Options                      | VESA via 4-hole 75mm mounting adapter on rear of unit.  |  |  |  |
| Temperature                           | Operating: 0° C to 40° C / 32°F to 104°F; Storage: -20° C to 60° C / -4°F to 140°F  |  |  |  |
| Humidity (non-condensing)             | Operating: 20% - 80% / Storage: 10% - 95% (38.7° C max wet bulb temperature)  |  |  |  |
| Regulatory approvals and declarations | Canada CUL, IC; Europe CE; Korea KCC; Taiwan BSMI; United States FCC, UL; Japan VCCI; International CB; Australia RCM; Mexico NOM; RoHS, China<br>RoHS, WEEE, REACH; United Kingdom UKCA  |  |  |  |
| Impact Protection                     | IK07  |  |  |  |
| Other Features                        | TUV Rhineland (Low Blue Light)<br>Power collection function via DDCCI   |  |  |  |
| Warranty                              | 3 years   |  |  |  |
| MTBF                                  | 50,000 hours demonstrated   |  |  |  |
| Extended Warranty Option              | 4 year warranty coverage - Elo P/N: E898247<br>5 year warranty coverage - Elo P/N: E898449<br>3 year warranty coverage + AUR - Elo P/N: E898648<br>4 year warranty coverage + AUR - Elo P/N: E894921<br>5 year warranty coverage + AUR - Elo P/N: E895125 |  |  |  |
| Box Content                           | 1004LS Touch monitor<br>Quick Install Guide<br>USB Type-C cable<br>75mm VESA adapter (assembled)  |  |  |  |

#### **Ordering Information**

| Part Number | Technology    | Surface Treatment | Touch Interface | Color     |
|-------------|---------------|-------------------|-----------------|-----------|
| E967935     | TouchPro PCAP | Anti-glare        | USB             | Dark Gray |

Learn more about Elo at **EloTouch.com**.

#### Americas

Tel +1 408 597 8000 elosales.na@elotouch.com

#### **Europe (EMEA)** Tel +32 16 930 136 EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385 m Elo.Asia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2024 Elo Touch Solutions, Inc. All rights reserved. 24122AES00205

