



# I-Series Steel for Android™

All-in-One Touchscreen



**Stainless Steel  
Enclosure**



**Android 12**



**IP65 Front &  
IP54 Back**

## Product Overview

Elo's I-Series Steel combines the durability of a stainless-steel chassis with the flexibility of Android. Complete with a chemically-strengthened touch display available in 10", 15" and 22" sizes, Android 12 OS, integrated PoE and superior IP ratings to protect the device from the demands of industrial environments and commercial kitchens.

With Google Mobile Services and EloView, managing Android devices and your apps is simplified. You can remotely deploy and manage your device, adjust detailed settings, and take advantage of the latest Google-powered features. Not only does this make management easier, but it also ensures your Elo devices meet the high standards required for Google CTS verification, giving you peace of mind.

**Available in 10", 15" or 22" widescreen sizes with an easy-to-clean edge-to-edge glass PCAP touchscreen**

**Integrated VESA for ease of mounting in portrait or landscape to a wall, pole, arm or any 3rd party compatible VESA mount**

**Fully integrated power-over-ethernet**

**Enterprise-Grade Support - Security updates, seamless provisioning, Elo Home, OEMConfig and more**

## I-Series Steel for Android AiO Touchscreen

| Specifications         | 10-inch model  | 15-inch model   | 22-inch model  |
|------------------------|--|---|--|
| Diagonal Size          | 10.1" / 256.54 mm  | 15.6" / 396.24 mm   | 21.5" / 546.10mm   |
| Operating System       | Android 12 with Google Play Services (AOSP capable)<br>Planned upgrade to Android 14 are available with an OS 360 subscription   |   |  |
| Processor              | Rockchip RK3399<br>Dual-core Cortex-A72 up to 1.8GHz<br>Quad-core Cortex-A53 up to 1.4GHz  |   |  |
| Memory                 | 4GB  |   |  |
| Storage                | 32GB   |   |  |
| I/O Ports              | 1x USB-A 3.0 support (900mA)<br>1x USB-C output*<br>1x RJ45 Ethernet LAN (Gigabit)<br>1x DC input(19v)<br>* When using the standard 65W power brick, USB-C can support up to 15W. When using the optional 90W power brick, USB-C can support up to 27W(10.1" can up to 15W). See User Manual for details   |   |  |
| Wireless               | 802.11a/b/g/n/ac + Bluetooth 5.0   |   |  |
| Webcam                 | 5MP, Max Resolution: 1920x1080 30fps, Auto Focus   |   |  |
| Speakers               | 2x 2W  | 2x 1.5W   |  |
| Audio                  | 1x built-in Analog Microphone  |   |  |
| Active Display Area    | 8.54" x 5.34" / 217 mm x 136 mm  | 13.55" x 7.62" / 344 mm x 194 mm                              | 18.74" x 10.54" / 476 mm x 268 mm                                |
| Resolution             | 1280 x 800 @ 60Hz  | 1920 x 1080 @ 60Hz  |  |
| Touch Technology       | TouchPro® PCAP (Projected Capacitive) - up to 10 touches   |   |  |
| Aspect Ratio           | 16:10  | 16:9  | 16:9   |
| Number of Colors       | 8-bit (16.7M)  |   |  |
| Brightness             | LCD Panel: 375 nits; PCAP: 322 nits  | LCD Panel: 250 nits; PCAP: 215 nits                           |  |
| Response Time          | 25 ms  |   | 14 ms  |
| Viewing Angle          | Horizontal: ±85° or 170° total /<br>Vertical: ±85° or 170° total   |   | Horizontal: ±85° or 170° total /<br>Vertical: ±80° or 160° total |
| Contrast Ratio         | 1000:1   | 700:1   | 1000:1   |
| Power                  | AC input voltage: 100-240 VAC; Input frequency: 50-60 Hz   |   |  |
| Power Consumption      | On: 7.1W; Off: 0.28W; Sleep: 1.04W   | On: 8.1W; Off: 0.33W; Sleep: 2.9W                             | On: 14.5W; Off: 0.3W; Sleep: 3.4W                                |
| Power Over Ethernet    | MAX 25.5W (for PoE models)   |   |  |
| Dimensions (W x D x H) | 10.34" x 7.06" x 1.35" /<br>262.58 mm x 179.38 mm x 34.28 mm   | 15.08" x 9.11" x 1.22" /<br>383 mm x 231.5 mm x 30.9 mm       | 20.98" x 12.75" x 1.75" /<br>533 mm x 324 mm x 44.4 mm           |
| Shipping Dimensions    | 13.9" x 6.81" x 10.63" /<br>353 mm x 173 mm x 270 mm   | 17.83" x 6.61" x 12.6" /<br>453 mm x 168 mm x 320 mm          | 24.13" x 6.81" x 16.34" /<br>613 mm x 173 mm x 415 mm            |
| Weight                 | 2.64 lbs / 1.2 kg  | 5 lbs / 2.27 kg   | 13.07 lbs / 5.93 kg  |
| Shipping Weight        | Without PoE: 6.83 lbs / 3.1 kg<br>With PoE: 4.85 lbs / 2.2 kg  | Without PoE: 9.24 lbs / 4.2 kg<br>With PoE: 7.92 lbs / 3.6 kg | Without PoE: 17.62 lbs / 8 kg<br>With PoE: 16.3 lbs / 7.4 kg     |
| Ingress Protection     | Front side IP65, Back side IP54  |   |  |
| Temperature            | Operating: 32°F to 113°F / 0°C to 45°C; Storage: -4°F to 122°F / 20°C to 50°C  |   |  |
| Humidity               | Operating: 20%-80%; Storage: 5%-95%  |   |  |
| Mounting Options       | VESA 75mm  | VESA 75mm and 100mm   |  |
| Real-Time Clock        | Lithium coin cell battery for real time clock  |   |  |
| MTBF                   | 50,000 hours   |   |  |
| Warranty               | 2 years standard   |   |  |
| Extended Warranty      | 3 year OS 360 - Elo P/N: E873133,<br>3 year - Elo P/N: E819394, 4 year - Elo P/N: E819598, 5 year - Elo P/N: E819795,<br>3 year + ADP - Elo P/N: E130329, 4 year + ADP - Elo P/N: E130530, 5 year + ADP - Elo P/N: E130719,<br>2 year + AUR - Elo P/N: E819985, 3 year + AUR - Elo P/N: E820186, 4 year + AUR - Elo P/N: E820388, 5 year + AUR - Elo P/N: E820582,<br>2 year + AUR + ADP - Elo P/N: E131490, 3 year + AUR + ADP - Elo P/N: E131674, 4 year + AUR + ADP - Elo P/N: E131859, 5 year + AUR + ADP - Elo P/N: E132053 |   |  |
| Security Updates       | Bi-monthly Android security updates available with Elo OS 360 package.   |   |  |
| Regulatory Approvals   | UL/FCC (US); cUL/IC (Canada); CE WEEE/UKCA (Europe); CB (International); VCCI/MIC (Japan); RCM (Australia); CCC/RoHS/SRRC (China)  |   |  |
| Supported Country List | Canada, USA, Australia, Japan, New Zealand, Austria, Belgium, Czech Republic, Denmark, France, Germany, United Kingdom, Hungary, Italy, Netherlands, Poland, Portugal, Romania, Spain, Sweden, Switzerland, Turkey, Brazil   |   |  |
| What's in the Box      | Without POE: I-Series Steel, North American Power Cable, European Power Cable, Power Brick, Quick Install Guide, 2x Cable tie<br>With POE: I-Series Steel, Quick Install Guide, 2x Cable tie   |   |  |

## Ordering Information

| Part Number | Size    | Processor       | OS         | PoE     | Memory | Storage |
|-------------|---------|-----------------|------------|---------|--------|---------|
| E725760     | 10-inch | Rockchip RK3399 | Android 12 | With    | 4GB    | 32GB    |
| E725963     | 10-inch | Rockchip RK3399 | Android 12 | Without |        |         |
| E724961     | 15-inch | Rockchip RK3399 | Android 12 | With    |        |         |
| E725164     | 15-inch | Rockchip RK3399 | Android 12 | Without |        |         |
| E725361     | 22-inch | Rockchip RK3399 | Android 12 | With    |        |         |
| E725554     | 22-inch | Rockchip RK3399 | Android 12 | Without |        |         |

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, Elo Edge Connect, EloView and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. Android is a trademark of Google LLC. Google Mobile Services is a trademark of Google LLC. All other trademarks are the property of their respective owners. © 2025 Elo Touch Solutions, Inc. All rights reserved. 25013AES00207

