



Power over Ethernet (PoE)

For I-Series 4 & 5 for Android



2-year warranty



**Compatible with
Android I-Series 4 & 5**



Power with POE

Product Overview

The Power-over-Ethernet (POE) module offers a convenient and cost effective way to deliver power to the I-Series 4 and 5 for Android. The module allows you to put a DC voltage onto specific pairs of the Ethernet cable so that devices connected to the network can use it as a power source. So instead of requiring a power drop which can be expensive, you can run a low voltage network to simplify installation of solutions for shelf signage and AV applications like conference room schedulers or AV control displays.

Power over Ethernet (PoE)

Specifications	
Color	Black
Compatibility	I-Series 4 and 5 for Android
Supported Standards	IEEE802.3, 10BASE T/IEEE802.3ab, 1000BASE-T/IEEE802.3u, 100BASE-TX, IEEE802.3at, IEEE802.3bt, Power over Ethernet
Transmission Media	Cat5 or higher per TIA/EIA-568
Efficiency	IEEE802.3at: Isolated power supply efficiency >85% IEEE802.3bt: Isolated power supply efficiency >79%
Customizable Settings	Panel Brightness, Wi-Fi/ Bluetooth, Audio, USB Port1 (type A), USB Port2 (type C), MicroUSB3, MicroUSB4, MicroUSB5, MicroUSB6, GPIO, External Display *Please refer to the User Manual for detailed information regarding default settings, product capabilities, and limitations.
Dimensions	Without 21.5" spacer: 3.46" x 3.46" x 0.74" / 88 mm x 88 mm x 18.8 mm With 21.5" spacer: 4.53" x 4.53" x 0.74" / 115 mm x 115 mm x 18.8 mm
Shipping Dimensions	Single box: 7.09" x 5.71" x 1.65" / 180 mm x 145 mm x 42 mm Carton: 14.76" x 12.2" x 16.73" / 375 mm x 310 mm x 425 mm
Weight	Without 21.5" spacer: 0.218 lbs / 0.099 kg With 21.5" spacer: 0.262 lbs / 0.119 kg
Shipping Weight	Single box: 0.511 lbs / 0.232 kg Carton: 18.396 lbs / 8.352 kg
Temperature	Operating: 0°C to 40°C (32°F to 104°F) Storage: -20°C to 70°C (-4°F to 158°F) Protection: OTP, OCP protection
Humidity (Non-Condensing)	Operating: 20% to 80% Storage: 10% to 95%
Regulatory Approvals and Declarations	FCC (US), IC (Canada), CE (Europe), VCCI (Japan), RCM (Australia)
Mounting Options	VESA 75mm and 100mm
Warranty	2 years
What's in the Box	POE Module Quick Install Guide 2x M3x8mm flat head screws (in a ziplock bag, labeled) 4x M4x12mm flat head screws (in a ziplock bag, labeled) 4x M4x12mm pan head screws (in a ziplock bag, labeled) 1x POE Spacer

Ordering Information

Part Number	Availability
E669163	Worldwide

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

