



# Z20 POS Stand

For I-Series 4 & 5 for Android



**Integrated I/O**



**Concealed Cable Routing**



**Flip the Display**

## Product Overview

The Z20 POS Stand delivers elegance to the point-of-sale. Complete with an integrated connectivity hub, concealed cable routing and the flexibility to either flip the main display from full service to self-service or add a fixed customer facing display on the back, the Z20 packs everything you need at the point of sale. Designed to support Elo's Android I-Series 4, the Z20 POS stand includes a universal VESA mount making it easy to install the 10- and 15-inch touchscreens with your choice of Qualcomm or Rockchip processor options.

Start changing the way customers and employees interact by deploying a new generation of interactive point-of-sale technologies that provide seamless integration, effortless provisioning and simplified device management via EloView or your preferred management tools.

**The flip stand design seamlessly converts the employee-facing full-service POS terminal to a customer-facing self-service kiosk**

**Integrated connectivity hub built into the stand with a compartment for seamless cable routing**

**Universal VESA mounts allow you to easily attach an employee-facing display and customer-facing display**

## Z20 POS Stand

Specifications	
Color	Black
Compatibility	<p>Main Display: 10-inch and 15-inch I-Series 4 &amp; 5 for Android</p> <p>Customer Facing Display: 1002L - Elo P/N: E155834 and E324341 1302L - Elo P/N: E683595 and E683787 1502L - Elo P/N: E125496</p> <p>*CFD supported on 15" model only</p>
Display Head Connection	USB Type C
I/O Ports	<p>Z20 POS Stand for 10" I-Series: 1x DC-Input, 2x USB-A 3.0 (900mA), 1x RJ12 (Cash drawer) * 12/24V, 1x RJ45 Ethernet LAN (Gigabit)</p> <p>Z20 POS Stand for 15" I-Series: 1x DC-Input, 4x USB-A 3.0 (900mA), 1x RJ12 (Cash drawer) * 12/24V, 1x RJ45 Ethernet LAN (Gigabit)**, 1x USB-C output - CFD (DisplayPort, Touch &amp; Power Delivery)***</p> <p>*User will need to select the mode **Ethernet upload and download speeds may decrease to ~250Mbps when using the CFD ***USB speeds may be reduced to 2.0 speeds when DisplayPort video is being output</p>
Pre-wired Cables	<p>19VDC cable to I-Series USB-C cable to connect to I-Series</p>
Power Input	<p>AC input voltage: 100-240 VAC Input frequency: 50-60 Hz</p>
Hinge Life Rating	5000 flips
Mounting Options	VESA 75 mm
Dimensions (W x D x H)	<p>Z20 POS Stand for 10" I-Series: 6.53" x 7.79" x 6.85" / 166 mm x 198 mm x 174 mm Z20 POS Stand for 15" I-Series: 7.6" x 10.0" x 6.7" / 194 mm x 255 mm x 169 mm</p>
Shipping Dimensions	12.36" x 11.93" x 12.4" / 314 mm x 303 mm x 315 mm
Weight	<p>Z20 POS Stand for 10" I-Series: 6.6 lbs / 3.0 kg Z20 POS Stand for 15" I-Series: 8.1 lbs / 3.7 kg</p>
Shipping Weight	<p>Z20 POS Stand for 10" I-Series: 9.4 lbs / 4.3 kg Z20 POS Stand for 15" I-Series: 11.4 lbs / 5.2 kg</p>
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C)
Humidity	Operating: 20%-80%; Storage: 5%-95%
Warranty	2 years standard
Extended Warranty	<p>3 year - Elo P/N: E375367, 4 year - Elo P/N: E375573, 5 year - Elo P/N: E375771 2 year + AUR - Elo P/N: E375970, 3 year + AUR - Elo P/N: E376169, 4 year + AUR - Elo P/N: E376362, 5 year + AUR - Elo P/N: E376547</p>
Regulatory Approvals	FCC (US); IC (Canada); CE (Europe); VCCI (Japan); RCM (Australia)
What's in the Box	<p>Z20 POS Stand for 10" I-Series: POS Stand; North American Power Cable; European Power Cable; Quick Install Guide; 90W Power Brick; VESA cover, top 10" (for mounting to the hinge); VESA cover, bottom 10" (for mounting to the hinge); Base Plate (for mounting to a countertop); Cable Tie (for securing cables); 1x Screw, M4x6 (in Bag "A" - for mounting VESA covers); 4x Screw, M4X8 (in Bag "B" - for mounting main display); 1x Screw, M3X6 (in Bag "C" - for mounting base plate)</p> <p>Z20 POS Stand for 15" I-Series: POS Stand; North American Power Cable; European Power Cable; Quick Install Guide; 150W Power Brick; 0.3m USB-C to USB-C Cable (To provide USB and Video signals to the CFD); VESA Cover, Top 15" (for mounting to the hinge); VESA Cover, bottom 15" (for mounting to the hinge); Base Plate (for mounting to a countertop); CFD Cover (for mounting a customer-facing display); Cable Tie (for securing cables); 1x Screw, M4x6 (in Bag "A" - for mounting VESA covers); 1x Screw, M4x6 (in Bag "A" - for mounting base plate); 4x Screw, M4X8 (in Bag "B" - for mounting main display); 4x Screw, M4X20 (in Bag "C" - for mounting a customer-facing display)</p>

## Ordering Information

Part Number	Model	Color
E554932	10" Z20 POS Stand	Black
E767356	15" Z20 POS Stand	Black

Learn more about Elo at [EloTouch.com](https://www.elotouch.com).

### Americas

Tel +1 408 597 8000  
elosales.na@elotouch.com

### Europe (EMEA)

Tel +32 16 930 136  
EMEA.Sales@elotouch.com

### Asia Pacific

Tel +86 (21) 3329 1385  
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. Android is a trademark of Google LLC. Google Mobile Services is a trademark of Google LLC. All other trademarks are the property of their respective owners. © 2025 Elo Touch Solutions, Inc. All rights reserved. 25044AES00215

