



按照 SAT11364 (电子电气产品有害物质限制使用标志要求)的规定,现将该产品的开保信息

都件名称	产品中有害物酸或元素的名称及合量				
	46	蒙	- 6	六价格	多溴联苯
	(Pb)	(Hg)	(C4)	(CF(A1))	(PBB)
型件 Plastic Part	0	0	- 0	0	0
铁件 Metal Part	0	0	- 0	0	- 0
無成电路 IC	0	0	- 0	0	0
二极管 Diode	0	0	- 0	0	0
晶体振荡器 Crystal	0	0	- 0	0	- 0
相用 Resister	X	0	- 0	0	0
电容 Capacitor	0	0	- 0	0	0
电板 Inductor	0	0	- 0	0	- 0
连接器 Connector	0	0	- 0	0	0
电路板 PCB	0	0	- 0	0	0
焊锡 Solder	0	0	0	0	0
软排线 FFC	0	0	- 0	0	0
持計 Wire Harness	0	0	- 0	0	0

①、股市市省等物价在3022种市红印的杜特平约介出902公司在6022公司在最级担价线量要是11字。 及中市场等物质型企作电路的约束。如此村村中约介金融区 6022公司在3023公司在3023公司程度要求 业中标页 X 的时有部件程序价效型 Rolis 法线。截出 GBT 20572 规定限量的密件事符 企业部分路免金款。 (改设分子由于均据设备中限制设用报告有事物验的 2011/85EU 均指令)

(1) 产品标准上的环程使用相限促zviromernal Protection Use Period, IPUP所以表示在北周间 內在正常標件条件下产品中所含有害物质或成分不会发生地漏和变异。因而此类产品的 使用不全导致任何严重的环境污染。任何人身份害或财产额失。同时不应将使期间视为

(2) 林瓷上带有污染控制林志的产品是可以回收的,不应随意进行处理。



www.elotouch.com

## **Quick Installation Guide**

# Barcode Scanner

Revision B P/N E202955

### **Elo Touch Solutions Technical Support**

Online self-help: www.support.elotouch.com

North America 800-ELO-TOUCH Tel +1 408 597 8000 Fax +1 408 597 8050 EloSales.NA@elotouch.com

Europe Tel +32 (0)16 70 45 00 Fax +32 (0)16 70 45 49 elosales@elotouch.com

**Asia-Pacific** Tel +86 (21) 3329 1385 Fax +86 (21) 3329 1400 EloAsia@elotouch.com

### Latin America

Tel 786-923-0251 Fax 305-931-0124 EloSales.LATAM@elotouch.com

The information in this document is subject to change without notice. Elo Touch Solutions, Inc. and its Affiliates (collectively "Elo") makes no representations or warranties with respect to the contents herein, and specifically disclaims any implied warranties of merchantability or fitness for a particular purpose. Elo reserves the right to revise this publication and to make changes from time to time in the content hereof without obligation of Elo to notify any person of such revisions or changes.

No part of this publication may be reproduced, transmitted, transcribed, stored in a retrieval system, or translated into any language or computer language, in any form or by any means, including, but not limited to, electronic, magnetic, optical, chemical, manual, or otherwise without prior written permission of Elo Touch Solutions, Inc.

Elo (logo) and Elo Touch Solutions are trademarks of Elo and its Affiliates





© 2017 Elo Touch Solutions, Inc. All rights reserved.

# Installation

Please go to www.elotouch.com/support to verify you have the latest drivers before installing this device.

### Notes

- 1. Place barcode a minimum of 40mm away from the scanner window for proper operation.
- 2. Software triggering of scanner not available on E267080.



Select the location to mount the barcode scanner. Some mounting locations not available on all systems.



Remove the selected peripheral cover from the display head to expose the peripheral bay.



Gently press the barcode scanner into the peripheral bay making sure the connector is mated.



Install the 2 flat head screws included with the kit.

Do not rotate the barcode scanner head without installing the screws or damage may occur.



Remove the protective film from the included mylar covers and place the covers over the screws.

Adjust the scanner angle as needed.