



- NOTES:**
1. ALL DIMENSIONS ARE IN MILLIMETERS AND INCHES.
  2. GLASS THICKNESS: 3.0±0.3mm [0.12±0.012]"
  3. TRANSDUCERS ARE LOCATED AT THE POSITIONS SHOWN. HEIGHT OF TRANSDUCER ABOVE GLASS: 1.6mm[0.06]" MAX. GLASS IS BEVELLED UNDER TRANSDUCERS.
  4. NO MATERIAL EXTENDS MORE THAN 0.8mm[0.03]" BEYOND THE BACK SURFACE OF THE GLASS.
  5. CABLE ROUTING (ALONG THE BEVEL) ADDS 2.5mm [0.10]" MAX. AS INDICATED ON THE SCREEN.
  6. BERG 65043-031, 2x6 HOUSING WITH BERG 48239-000 RECEPTACLES, DIRECTLY MATES WITH ANY OF THE FOLLOWING:
    - INTELLITOUCH SERIAL CONTROL BOARD
    - 012226 CABLE (2x6 TO 8" DB9 BULKHEAD)
  7. CABLE JACKET STRIPPED 152mm[6.0]" FOR EASE DURING THE INTEGRATION PROCESS.
  8. NO SEALING ALLOWED, THEREFORE NO PROTECTION AGAINST DUST AND SPILLS; REGULAR CLEANING IS REQUIRED.

CONNECTION CHART			
PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		
3	Y RECEIVE (+)	BLU	BLK
4	Y TRANSMIT (+)	BLU	GRY
5	Y RECEIVE (-)	BLK	BLK
6	Y TRANSMIT (-)	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT (-)	RED	RED
9	X RECEIVE (-)	RED	BLK
10	X TRANSMIT (+)	GRN	RED
11	X RECEIVE (+)	WHT	BLK
12	KEY		

TOUCHSCREEN TABULATION	
PART NO	SURFACE FINISH
E259081	ANTI-GLARE

