



PIN	SIGNAL	INSULATION COLOR	JACKET COLOR
1	GROUND	OVERALL SHIELD	
2	KEY		BLK
3	Y RECEIVE (+)	BLU	BLK
4	Y TRANSMIT (+)	BLU	GRY
5	Y RECEIVE (-)	BLK	BLK
6	Y TRANSMIT (-)	YEL	GRY
7	GROUND	INNER SHIELD	
8	X TRANSMIT (-)	RED	RED
9	X RECEIVE (-)	RED	BLK
10	X TRANSMIT (+)	GRN	RED
11	X RECEIVE (+)	WHT	RED
12	KEY		BLK

NOTES:

- 1 ALL DIMENSIONS ARE IN MILLIMETERS.
- 2 GLASS THICKNESS: 2.8.
- 3 TRANSDUCER KEEP OUT AREAS PER DETAIL B THRU D.
- 4 HEIGHT OF TRANSDUCERS ABOVE GLASS: 3.2 MAX.
- 5 NO MATERIAL EXTENDS MORE THAN 0.8 BEYOND THE BACK SURFACE OF THE GLASS.
- 6 BERG 65043-031, 2 X 6 HOUSING WITH BERG 48239-000 RECEPTACLE, DIRECTLY MATES WITH ANY OF THE FOLLOWING: >INTELLITOUCH SERIAL CONTROL BOARD >012226 CABLE (2 X 6 TO 8" DB9 BULKHEAD)
- 7 MOUNTING TAPE, 5.0 WIDE 3M VHB 4920, TO BE APPROXIMATELY CENTERED IN THE MOUNTING AREA.
- 8 SCREEN IS DESIGNED TO FIT INTO A 23.0" LCD (WIDE FORMAT 16:9 ASPECT RATIO).

LOC 08  
DIST 08

3859-7 (3/11) 8 7 6 5 4 3 2 1

P	LTN	REVISION RECORD	DATE	BY	APP'D
A	INITIAL	RELEASE ECD-13-001396	01/07/13		

DIMENSIONS (MM)		DIMENSIONS (INCHES)	
0	PLC ±	0	PLC ±
1	PLC ±	1	PLC ±
2	PLC ±	2	PLC ±
3	PLC ±	3	PLC ±
4	PLC ±	4	PLC ±
5	PLC ±	5	PLC ±
6	PLC ±	6	PLC ±
7	PLC ±	7	PLC ±
8	PLC ±	8	PLC ±
9	PLC ±	9	PLC ±
10	PLC ±	10	PLC ±
11	PLC ±	11	PLC ±
12	PLC ±	12	PLC ±

REV	DATE	DESCRIPTION	BY	APP'D
1	08/03/12	INITIAL		
2	01/07/13	D.I.	A.V.	
3	01/07/13	APP'D	A	

SCALE 1:1 SIZE A2 SHEET 1 OF 1

MS601396

DIMENSIONAL DRAWING, SCN-II-EZW3.0-014-020-R

THIS INFORMATION IS CONFIDENTIAL AND PROPRIETARY TO ELD TOUCH SOLUTIONS INC AND ITS VENDORS. IT MAY NOT BE DISCLOSED TO ANYONE, OTHER THAN ELD PERSONNEL, WITHOUT AUTHORIZATION FROM ELD. WWW.ELDTOUCH.COM