



1291L 12.1-inch LCD

Open-Frame Touchscreen



Integrated Touch



Commercial Grade



3-Year Warranty

Product Overview

The Elo 1291L 12.1-inch open-frame LCD touchscreen features a slim design and narrow outside dimensions thanks to the state-of-the-art, energy-saving LED backlight, using less electricity to operate and generating less heat. This compact display is designed for touch with proven Elo expertise and reliability built in. The 1291L provides stable, drift-free operation with outstanding image clarity and light transmission for accurate touch responses and vivid images. Featuring a brilliant wide viewing angle panel, the open-frame touchscreen instantly grabs and holds the users' attention for kiosks, casino and amusement, retail self-service, and industrial automation environments.

**Choice of Elo touch technologies:
Standard bezel: IntelliTouch[®] SAW
Zero-bezel: TouchPro™ PCAP**

Elo's TouchPro PCAP offers:

- **2GS (two glass solution) with pristine optical clarity and touch durability.**
- **10 touch with thru-glass capabilities that passes UL-60950 & IK-07 impact testing**

Video Interfaces: HDMI, VGA & Display Port

1291L 12.1-inch Open-Frame Touchscreen

Specifications	
Model	1291L
Color	Black
Active Display Area	9.69" x 7.26" / 246mm x 184.50mm
Diagonal	12.1"
Aspect Ratio	4:3
Dimensions	IntelliTouch: 11.91" x 9.54" x 1.96" / 302.5mm x 242.2mm x 49.8mm PCAP: 11.90" x 9.53" x 1.77" / 302.5mm x 242mm x 44.9mm
Native Resolution	800 x 600 at 60Hz
Other Supported Resolutions	640 x 480 at 60Hz; 800 x 500 at 60Hz
Number of Colors	16.2 million
Number of Touches	Single-touch and 10-touch
Brightness (typical)	LCD Panel: 450 nits; IntelliTouch: 405 nits; TouchPro PCAP: 405 nits
Response (typical)	25 msec
Viewing Angle	Horizontal: 89° / 178°; Vertical: 89° / 178°
Contrast Ratio	1500:1
On-Screen Display	Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select, Power Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color, Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD V-Position, Recall Defaults, Video Priority, Information, Touch On Sleep Mode, Touch Through Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese Lockouts: OSD, Power
Video	HDMI V1.3 Type A receptacle for HDMI input Analog VGA on Female DB-15 connector DisplayPort V1.1a - Supports later versions of Display Port video input Input Video Horizontal Sync frequency range: 30 - 38KHz Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	External DC - Optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2.0mm (+0.0 -0.1mm) pin outer diameter, 6.4mm (+/- 0.3mm) barrel inner diameter, 8.8mm (+/- 0.3mm) barrel depth) Monitor input power signal specifications: 12VDC +/- 5%
Power Consumption	ON (monitor + power brick): 12.2W SLEEP (monitor + power brick): 1.5W OFF (monitor + power brick): 0.5W
Temperature	Operating: 0 °C to 40 °C (32 °F to 104 °F); Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	Operating: 20% to 80%; Storage: 10% to 95%
Weight	Unpackaged: 5.8 lbs / 2.65 kg; Packaged: 10.5 lbs / 4.75 kg
Shipping Dimensions	15.12" x 12.68" x 14.38" / 384mm x 322mm x 185mm
Mounting Options	VESA 4-hole 75mm; Rear mount through bezel or with included mounting brackets (IntelliTouch models); Flush mount with included mounting brackets (TouchPro PCAP Models)
Warranty	3 years standard
MTBF	50,000 hours demonstrated
Agency Approvals	UL, FCC; RCM; cUL, IC; CCC; CE, TUV; VCCI; KCC; CoC; BSMI; CB; RoHS, China RoHS, WEEE, IMERC
What's in the Box	HDMI Cable, VGA Cable, OSD Remote, Touch USB Cable, User Manual CD and Quick Install Guide; For Zero-Bezel Models: Flush Mount Brackets w/ Screws; For Bezeled Models: "L" (Side Mount) Brackets w/Screws, EEI Label, Japan Class-B TM info sheet

Ordering Information

Model	Part Number	Part Description	Technology	Interface	Surface Treatment	Video Interface	Availability
1291L	E331595	ET1291L-2UWB-0-MT-ZB-NPB-G	TouchPro PCAP	USB	Clear	HDMI, VGA & Display Port	Worldwide
	E329452	ET1291L-8CWB-1-ST-NPB-G	IntelliTouch	Dual serial/USB	Anti-Glare	HDMI, VGA & Display Port	Worldwide

Extended Warranty Options

Part Number	Description
758588-000	1 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
930057-000	2 Year Extended Warranty, 7-inch to 22-inch LCD Touchmonitor
E67295-000	Elo advance unit replacement for touchmonitors

To find out more about our extensive range of Elo touch solutions, go to elotouch.com, or call the office nearest you.

North America

Tel +1 408 597 8000
Fax +1 408 597 8050
elosales.na@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
elosales.latam@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo IntelliTouch and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners. © 2017 Elo Touch Solutions, Inc. All rights reserved. 17034AES00046

