

- Sensitive touch performance with “Built for Touch” reliability
- Choice of touchscreen technology
- Commercial durability
- 3 year standard warranty



2243L 22” Open-Frame Touchmonitor

The Elo Touch Solutions 2243L open-frame LCD touchmonitor features a slim design and narrow outside dimensions due to the state-of-the-art energy-saving LED backlight, using less electricity to operate and generating less heat. Wide-aspect displays like the 2243L, allow extra content on the screen and are frequently used in casino gaming, amusement and entertainment settings as well as public venue environments due to the high-definition cinematic-like experience. Typical applications for the 2243L include: gaming and amusement, information kiosks and selfservice, as well as interactive digital signage applications.

Available with IntelliTouch Plus multi-touch surface acoustic wave (SAW) touchscreen technology, IntelliTouch single-touch SAW, SecureTouch anti-

vandal SAW as well as IntelliTouch Zero-Bezel SAW and IntelliTouch Pro projected capacitive for a true flat look, the 2243L is compatible with Windows 7 and 8, and provides stable “drift-free” operation with outstanding image clarity and light transmission—for accurate touch responses and vivid images. Each touchscreen uses scratch-resistant pure-glass construction that delivers a clear, bright and long-lasting performance. With a compact design and multiple mounting options the 2243L is easy to integrate into a variety of configurations. It also features a unique, injection-molded mini-bezel for a virtually invisible water resistant seal which gives integrators an edge in developing aesthetically-pleasing solutions.



Features

- Choice of touch technologies:
 - Standard bezel:** IntelliTouch and IntelliTouch Plus surface acoustic wave, SecureTouch anti-vandal surface acoustic wave
 - Zero-Bezel:** IntelliTouch Zero-Bezel surface acoustic wave and IntelliTouch Pro projected capacitive
- Slimmer dimensions enables thinner, artistic enclosure designs
- High definition LCD display offers ultimate HD interactivity, clarity and resolution
- 16:9 aspect ratio and bright 250 nits panel for a larger display surface and bright vivid images
- LED backlighting allows for state-of-the-art slim design while reducing power consumption
- Optimized for use in high-traffic environments

Applications

- Gaming machines
- Kiosks
- Point-of-Information
- Self-service and ticketing

About Elo

Elo founders pioneered the touchscreen over 40 years ago. Today, Elo Touch Solutions is a leading global supplier of touch-enabled technology, products and industry solutions. The Elo portfolio encompasses the broadest selection of OEM touchscreen components, touchmonitors, and all-in-one touchcomputers for the demanding requirements of diverse markets, including gaming machines, hospitality systems, industrial automation, interactive kiosks, healthcare, office equipment, point of sale terminals, retail displays, and transportation applications. The Elo touch experience has consistently stood for quality, reliability and innovation with over 20 million installations worldwide.

2243L 22" Open-Frame Touchmonitor Specifications

Specifications	
Model	2243L
Bezel Color	Black
Diagonal Size	21.5" diagonal
Aspect Ratio	16:9
Active Display Area	18.8" x 10.6" (477mm x 268mm)
Dimensions*	IntelliTouch/SecureTouch: 20.2" x 11.7" x 1.7" (512 x 298 x 43 mm) IntelliTouch Pro: 20.3" x 12.2" x 1.5" (516 x 311 x 38.5 mm) IntelliTouch ZB: 20.7" x 12.4" x 1.6" (526 x 317 x 40.4 mm)
LCD Technology	Active matrix TFT LCD with LED backlighting
Native Resolution	1920 x 1080
Other Supported Resolutions	640x480 60Hz; 720x576 50Hz; 800x600 56, 60Hz; 1024x768 60Hz; 1280x720 50, 60Hz; 1280x960 60Hz; 1280x1024 60Hz; 1366x768 60Hz; 1440x900 60Hz; 1680x1050 60Hz; 1920x1080 50, 60Hz
Colors	16.7 million
Brightness (Typical)	LCD Panel: 250 nits; with IntelliTouch: 225 nits; with IntelliTouch Plus: 225 nits; with PCAP: 225 nits; SecureTouch: 225 nits; with IntelliTouch ZB: 225 nits
On-Screen Display (OSD)	Accessible through switches on the unit's tethered OSD Control box. Controls: Menu, Up, Down, Select; Settings: Brightness, Contrast, Clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature, OSD Timeout, OSD Language, OSD H-Position, OSD; V-Position, Recall Defaults, Video Source; Languages: English, French, Italian, German, Spanish, Simplified Chinese, Traditional Chinese, Japanese; Lockouts: OSD, Power
Response Time ((Tr + Tf) (Typical)	5 ms
Viewing Angle (Typical)	Horizontal: ±85°; Vertical: ±80°
Contrast Ratio (Typical)	1000:1
Video	Analog VGA on Female DE-15 connector; Digital DVI on Female DVI-D connector; Input Video Horizontal Sync frequency range: 31.5-80KHz; Input Video Vertical Sync (frame rate) frequency range: 50-75Hz
Power	External DC—optional power brick (sold separately) Monitor input power connector: Coaxial power jack (2mm pin outer diameter, 6.4mm barrel inner diameter); Monitor input power signal specifications: 12VDC ± 5% Adapter input connector: IEC 60320 C14; Adapter input voltage range: 100-240VAC, 50/60Hz Power Consumption (typical); ON (monitor only): 22W; ON (monitor + AC/DC adapter at 230V/50Hz): 25W SLEEP (monitor + AC/DC adapter at 230V/50Hz): 2.2W OFF (monitor + AC/DC adapter at 230V/50Hz): 1.1W
Temperature	Operating: 32°F to 104°F (0°C to 40°C); Storage: (-4°F to 140°F) -20°C to 60°C
Humidity (Non-Condensing)	Operating: 20%-80%; Storage: 10%-90%
Weight	Unpackaged: 10.6lbs (4.8kg); Packaged: 15.3lbs (6.9kg)
Shipping Dimensions	7.9" x 24.4" x 16.9" (200mm x 620mm x 430mm)
Warranty	3 years
MTBF	50,000 hours demonstrated
User's Controls	Optional remote OSD: Auto/Sel, up, down, menu; OSD buttons: menu, left, right, select, power; OSD: contrast, brightness, H/V position, RGB (color temp), clock, phase, recall, language (English, German, Spanish, Japanese, French); OSD disable/enable: power, OSD menu
Mounting Options*	VESA 4-hole 100mm mounting interface on rear of unit 2-hole mounting interface on all 4 sides
Regulatory Approvals and Declarations	S-Mark; C-Tick; cUL, IC; CCC; CE; VCCI; KCC; NOM; BSMI; UL, FCC; CB; RoHS, China RoHS, WEEE, IMERC

*See dimensional drawings for details

Ordering Information

Part Number	Technology	Interface	Bezel	Input Video Format	Surface Treatment
E237584	IntelliTouch Plus Dual touch	USB	Yes	DVI/Analog VGA	Clear
E059181	IntelliTouch Single touch	USB	Yes	DVI/Analog VGA	Clear
E811441	IntelliTouch Pro PCAP Multi touch	USB	No	DVI/Analog VGA	Clear
E001114	IntelliTouch ZB Single touch	Serial/USB	No	DVI/Analog VGA	Clear
E378034	SecureTouch	USB	Yes	DVI/Analog VGA	Clear

To find out more about our extensive range of Elo touch solutions, go to www.elotouch.com, or call the office nearest you.

North America

Elo Touch Solutions
1033 McCarthy Boulevard
Milpitas, CA 95035

800-ELO-TOUCH

Tel +1 408 597 8000
Fax +1 408 597 8001
customerservice@elotouch.com

Europe

Tel +32 (0)16 70 45 00
Fax +32 (0)16 70 45 49
elosales@elotouch.com

Asia-Pacific

Tel +86 (21) 3329 1385
Fax +86 (21) 3329 1400
www.elotouch.com.cn

Latin America

Tel +1 786-923-0251
Fax +1 305-931-0124
www.elotouch.com

Elo Touch Solutions, Inc. reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo (logo) and Elo Touch Solutions are trademarks of Elo Touch Solutions, Inc. © 2015 Elo Touch Solutions, Inc. All rights reserved. 15111AES00006

